



# Data Sheet

## LIFEPAK® CR2 Defibrillator with LIFELINKcentral™ AED Program Manager

- Self-monitoring
- Wireless connectivity
- Fastest time to first shock<sup>1</sup>
- cprINSIGHT™ Analysis Technology
- Layered, easy to follow design



Sudden cardiac arrest (SCA) can happen to anyone—anywhere. Immediate treatment is vital. A victim's chance of survival dramatically decreases for every minute without treatment.<sup>2</sup> That's why public access defibrillators are so important. They put lifesaving technology where it can do the most good. So when an emergency happens, you should have nothing less than the best.

- **Layered design**  
Layered design with easy to follow bold graphics. Both trained and untrained AED users clearly know how to begin.
- **QUIK-STEP™ electrodes**  
Peel directly off the base for faster placement.
- **cprINSIGHT analysis technology**  
Analyses for shockable rhythm during chest compressions with no need to pause.
- **Metronome and CPR coaching**  
Sets an effective pace and audibly guides users.
- **ClearVoice™ technology**  
Detects background noise and adjusts volume accordingly for clear instruction.
- **Fully automatic**  
Available in fully or semi-automatic models.
- **Highest available escalating energy**  
Up to 360J for more effective shocks as needed.
- **Bilingual**  
Toggle between two pre-set languages when using the device.
- **Child mode**  
Child mode delivers lower energy levels appropriate for young children without having to change electrodes.
- **LIFEPAK TOUGH™**  
IP55 rating for challenging environments.
- **8-year warranty**  
Backed by an 8-year warranty.
- **LIFELINKcentral AED Program Manager**  
Monitor AED programs by tracking AED status, sending patient data to emergency responders and hospitals, detecting AED locations and other tools.



# LIFEPAK® CR2 Defibrillator

## Defibrillator

**Waveform:** Biphasic Truncated Exponential with voltage and duration compensation for patient impedance.

**Patient Impedance Range:** 10 – 300 ohms

**Energy Accuracy:**

10% of the energy setting into 50 ohms

15% of the rated energy output into 25 – 175 ohms

**Output Energy Sequence:** Multiple levels, configurable from 150 joules to 360 joules.

**Energy Default:** 200J, 300J, 360J (adult)  
50J, 75J, 90J (paediatric)

**Shock Advisory System™:** An ECG analysis system that advises whether a shock is appropriate; meets rhythm recognition criteria specified in IEC 60601-2-4.

**cprINSIGHT™ Analysis Technology:** Enables the defibrillator to analyse the patient's heart rhythm while CPR is being performed.

**CPR Coaching:** Instructions for adult and paediatric CPR, including feedback when no CPR is detected, rate and depth guidance, a metronome and instructions on hand placement.

**Time to Shock at 360J after CPR (with cprINSIGHT enabled):**

- **Semi-Automatic:** < 7 seconds

- **Fully Automatic:** < 13 seconds

**Charge Time:** 0 seconds for first 150J or 200J shock (as device is pre-charged). With cprINSIGHT enabled, subsequent shocks will be charged during CPR and ready to shock at the end of the CPR period.

## Controls

**Lid Release/ON-OFF:** Controls device power.

**Shock button, Semi-automatic:** Delivers energy when button pressed by the user.

**Shock button, Fully Automatic:** Flashes prior to delivering shock without requiring user intervention.

**Child Mode Button:** Allows operator to switch to Child Mode for reduced energy and CPR guidance appropriate for children.

## References

1 Physio-Control Internal Semi-Automatic AED Comparison Usability Study, August 2016.

2 Graham R, McCoy M, Schultz A. Strategies to Improve Cardiac Arrest Survival, A Time to Act. Institute of Medicine Report, 2015.

If you purchased your LIFEPAK CR2 Defibrillator from an authorized Physio-Control distributor or reseller, this distributor or reseller will have access to your LIFELINKcentral AED Program Manager account and may receive notifications prompted by the LIFEPAK CR2 Defibrillator. Please note that this setting can be disabled at ANY time: if you wish to disable this setting, please send a request to Physio-Control Customer Support to change the Distributor value to "Customer Managed".

Although not everyone can be saved, studies show that early defibrillation can dramatically improve survival rates.

All claims valid as of August 2016.

For further information please contact your local Physio-Control representative or visit our website at [www.physio-control.com](http://www.physio-control.com).

# Specifications

## Physical Characteristics

**With handle, including electrodes and battery:**

**Height:** 9.7 cm (3.8 in)

**Width:** 22.6 cm (8.9 in)

**Depth:** 27.4 cm (10.8 in)

**Weight:** 2.0 kg (4.5 lb)

## Accessories

### PRIMARY BATTERY

**Type:** Lithium Manganese Dioxide (Li/MnO<sub>2</sub>), 12.0V, 4.7 amp-hours.

**Capacity (at 20°C):** Will provide 166 200 joule shocks (with one minute of CPR between shocks) or 103 360 joules shocks (with one minute of CPR between shocks) or 800 minutes of operating time.

**Standby Life (assuming daily tests only):** A new battery provides device power for 4 years if installed in device that is not used.

**Replace Battery Indication:** At least 6 shocks and 30 minutes of operating time remain when first indicated.

**Weight:** 0.3 kg (0.7 lb).

### ELECTRODE PADS

**Pads:** Can be used on both adult and paediatric patients.

**Pads Packaging:** User intuitive, rapid access electrodes.

**Pads Replacement:** Replace every 4 years.

## Data Storage

**Memory Type:** Internal digital memory (flash RAM).

**ECG Storage:** Minimum 60 minutes of ECG stored for two patient episodes.

## Communications

**Communications:** USB Wireless 802.11 b/g/n, or Cellular data transfer to LIFELINKcentral™ AED Program Manager or LIFENET® System.



**Physio-Control Headquarters**  
11811 Willows Road NE  
Redmond, WA 98052 USA  
Tel 425 867 4000  
Fax 425 867 4121  
[www.physio-control.com](http://www.physio-control.com)

**Physio-Control Operations Netherlands B.V.**   
Galjoenweg 68  
6222 NV Maastricht  
The Netherlands  
Tel +31 (0)43 3620008  
Fax +31 (0)43 3632001

**Physio-Control UK Sales Ltd**  
11 Old Jewry, 7th Floor  
London EC2R 8DU  
United Kingdom

**Physio-Control Australia Pty Ltd**  
Suite 4.01, 15 Orion Rd.  
Lane Cove, NSW 2066  
Australia  
Toll Free Tel 1800 987 982  
Toll Free Fax 1800 890 892



Physio-Control, Inc., 11811 Willows Road NE, Redmond, WA 98052 USA

